The Delphion Integrated View

Get Now: PDF More choices	Tools: Add to Work File	Create new Wo
View: Expand Details INPADOC Jump to: Top	Go to: Derwent	⊠ <u>Ema</u>

Title: EP0436792B1: Press for making dimensionally stable pressed article

particulate material[German][French]

Derwent Title: Powder blank press for mfg. blanks - has pot die carriers to give true to

size stepped profiles with non-stick die action [Derwent Record]

PCountry: **EP** European Patent Office (EPO)

Finventor: Fleissner, Roland;

Krumpholz, Georg;

Assignee: Dorst Maschinen und Anlagenbau Otto Dorst und Dipl.-Ing Walter

Schlegel GmbH & Co.

News, Profiles, Stocks and More about this company

Published / Filed: 1994-05-25 / 1990-11-05

₽ Application **EP1990000121145**

Number:

PIPC Code: B30B 11/02;

@ECLA Code: B30B11/02;

Priority Number: 1990-01-09 <u>DE1990004000423</u>

Abstract: [From equivalent EP0436792A2] In a press with an upper and a

lower press ram and a tool frame which can be inserted into the press in the manner of an adapter, the stamp supports of the tool frame are formed by pots which are guided on cylindrical surfaces

relative to the baseplate of the tool frame.

*Attorney, Agent Herrmann-Trentepohl, Werner, Dipl.-Ing. et al;

or Firm:

Legal Status:

PDesignated AT CH FR GB IT LI SE

Country:

Family: Show 8 known family members

First Claim: Show all claims 1. A press for making dimensionally stable

pressed articles from particulated material especially ferruginous powder or ceramic powder, with an upper press ram and a lower press ram and a tool frame (2) which is capable of being adjustably inserted into the press and attached by means of a lower coupling plate (3) on the lower ram and by means of an upper connecting piece (6) on the upper ram, and which comprises, on a base plate (1) of the tool frame (2), with said base plate being firmly supported within the press, an adjustably positioned framework of tie rods (5) preferably connecting the lower coupling plate (3) rigidly with the



matrix retaining plate (4) as well as with die holders which, by means of a piston/cylinder drive, are movable upwardly from the base plate (1) into the fill and press position, characterised in that the die holders are constructed as chambers (8, 9, 10) which are carried on cylindrical surfaces (at 15, 16, 18) relative to the base plate (1).

[German] [French]

¥Other Abstract Info:

POther Abstract DERABS C91-209244











this for the Gallery...

© 1997-2004 Thomson

Research Subscriptions | Privacy Policy | Terms & Conditions | Site Map | Contact Us | F